

# lion alcolmeter® SL-400



*...a breath alcohol screening instrument for field use - anywhere! ...fast ...simple ...accurate!*

## Instrument Features

- **SIMPLE TO USE:** the lion alcolmeter® SL-400 is fully automatic. This means it's very simple to use, so training requirements are minimal.
- **FAST, ACCURATE ANALYSIS:** using the Lion *fuel cell* sensor. This ensures high specificity to alcohol, and a long stable working life.
- **EASY TO READ DISPLAY:** alcohol readings are shown on four coloured LED's - **ZERO, PASS, WARN** and **FAIL**. Four indicator lights inform and instruct the operator, and a small LCD shows the date/time and memory levels.
- **LAST TEST RECALL OPTION:** the result of the last breath test can be recalled, even if the instrument has since been switched off (not in UK Police version).
- **AUTOMATIC DATA COLLECTION:** readings are stored in memory, with date and time, and can be downloaded to a printer or PC.
- **CALIBRATION SECURITY:** by means of the 'dongle' electronic key.
- **HOME OFFICE APPROVED:** the lion alcolmeter® SL-400 is Approved by the Home Office for Police use in Great Britain.




# Simple Operating Procedure!




**1**  
SWITCH ON:  
AUTOMATIC SELF CHECK



**2**  
ATTACH MOUTHPIECE:  
INSTRUCT THE SUBJECT



**3**  
THE SUBJECT BLOWS



**4**  
NOTE ALCOHOL READING

## Advanced Specifications and Features

- **Fuel Cell Sensor:** high specificity to alcohol, unaffected by other possible breath contaminants.
- **Warm-up Time:** the instrument is ready for use within 15 seconds of switch on, at **any** temperature.
- **Analytical Response Time:** normally within 30 seconds; but within 5 seconds at zero alcohol levels.
- **Temperature Range:** from -5°C to +40°C, for optimum operation.
- **Recalibration:** every six months, using either a wet-bath simulator or **AlcoCal**® gas standard.
- **Recovery Time:** typically 10 seconds at zero alcohol; 60 seconds at 0.35mg/litre BrAC; 4 minutes at 2.00mg/litre.
- **Memory Capacity:** 150 breath tests.
- **Power Supply:** 5 new AA cells give at least 3,000 breath tests. Two stage low power warning system.
- **Radio Frequency Immunity:** exceeds requirement of EN 50082-1.
- **Shock/Vibration:** impact resistant ABS: meets IEC 68-2-27 Part 2.1 Test EA and IEC 68-2-6 Part 2.1 Test FC.
- **Dimensions:** 169 x 80 x 39mm [instrument only]; 190 x 90 x 65mm [in leather pouch].
- **Weight:** approximately 525g [including batteries and leather pouch].
- **Date and Time:** each test result is stored with date and time [internal battery backed].

## Accessory Items

- **Disposable Mouthpieces:** low resistance to breath flow; individually and hygienically wrapped.
- **Leather Pouch:** in either grey or reflective yellow.
- **Rechargeable Power Unit:** with 220 volts AC/12 volts DC intelligent charger.
- **Vehicle Power Unit:** operate the **400** from a vehicle's 12 volt DC supply [via the lighter socket].
- **Data Printer:** prints stored data from memory.
- **Handbooks:** covering all aspects of use.

## Accessory PC Software

- **Data-400™ :** retrieve test data from memory and store it on your PC's hard disk; then export to any standard database or spread sheet program. Operates under MS Windows. Supplied with connector cable and full instructions.
- **DataMac-400™ :** the same application as for **Data-400™**, but used in Apple Macintosh PC systems. Supplied with connector cable and full instructions.



INVESTOR IN PEOPLE



Lion Laboratories Limited

TY VERLON INDUSTRIAL ESTATE, BARRY, SOUTH GLAMORGAN, **CF63 2BE**, WALES, UNITED KINGDOM  
TELEPHONE (+44) (0)1446 744244 FAX (+44) (0)1446 720937 WEB [www.lion-breath.com](http://www.lion-breath.com) E-MAIL [sales@lion-breath.com](mailto:sales@lion-breath.com)

CE 0086

Complies with directive  
93/42/EEC



FM 25502  
CERTIFIED TO  
INTERNATIONAL QUALITY  
STANDARD ISO 9000:  
EN 29000 : BS 5750